

	3460	3461	AC5465	AC5466
Colour	Whitish	Whitish	Transparent at 0 gap	Translucent
Odour	Typical Acrylate	Typical Acrylate	Typical Acrylate	No odor
Shelf life	6 months @ RT	6 months @ RT	12 months @RT	12 months @RT
Adhesion on substrates	Good on all substrates. Superior on PP & PE	Good on all substrates. Superior on PP & PE	Good on most substrates. Superior on metal-plastic bonding	Good on most substrates. Superior on mixed bonding
PP	EXCELLENT	EXCELLENT	EXCELLENT	EXCELLENT
PE	EXCELLENT	EXCELLENT	EXCELLENT	EXCELLENT
PTFE	GOOD	EXCELLENT	EXCELLENT	GOOD
РММА	GOOD	GOOD	EXCELLENT	GOOD
PEEK	-	-	EXCELLENT	EXCELLENT
Acetal (POM)	-	-	GOOD	EXCELLENT
Nylon	<u> -</u>	-	EXCELLENT	EXCELLENT
Composites	GOOD	GOOD	GOOD	GOOD
Metal	GOOD	GOOD	EXCELLENT	GOOD
Glass	GOOD	GOOD	GOOD	-
Leather	-	-	GOOD	-
Wood	GOOD	GOOD	GOOD	-
Peel strength	+++	+++	+++	++
Packaging availability	Cartridges - 50ml Cartridges - 400ml Bulk upon request	Cartridges - 50ml Cartridges - 400ml Bulk upon request	Cartridges - 50ml Cartridges - 400ml Bulk upon request	Syringes - 25ml Cartridges - 50ml Cartridges - 400ml Bulk upon request
Best choice	When very fast speed is required	Superior cost/perfomances balance	When transparent bondline is needed. Multipurpose, ok for both OEM and MRO	No unpleasant odour during application and after cure. Multipurpose, ok for both OEM and MRO

EXAMPLES:

- LAMPS,
- HOUSEHOLD APPLIANCES,
- FURNITURE,
- SENSOR COMPONENTS,
- AUTOMOTIVE COMPONENTS,
- SPORTS EQUIPMENT,
- BONDING PE / PTFE GUIDES ON STEEL,
- SEALING PE / PP JOINTS (Water, ad Blue, etc.),
- ACETALIC GLASSES, ETC.





